

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (currently amended) A method of monitoring and controlling data transfer between a user terminal coupled to a first communication network and a second communication network, said first communication network coupled to said second communication network via a gateway and a firewall, said method including the steps of:

sending an access request to said gateway from said user terminal requiring access to said second communication network;

said gateway reading said access request;

modifying at least one access rule in said firewall to permit access for said user terminal requesting access based on an authenticated IP address of said user terminal requesting access, said authenticated IP address including authentication of a user;

monitoring ~~simultaneously~~ at said firewall the transfer of data between said user terminal and said second communication network; and

dynamically controlling, in real time, bandwidth available to said user terminal at least on the basis of the authenticated user.
2. (previously presented) The method of claim 1, wherein said dynamic control of bandwidth available to said user terminal occurs whilst maintaining communication

of said user terminal with said second communication network.

3. (previously presented) The method of claim 1, wherein a restricted bandwidth is allocated to a single user terminal.
4. (previously presented) The method of claim 1, wherein a restricted bandwidth is shared between a plurality of user terminals.
5. (previously presented) The method of claim 1, wherein bandwidth is restricted for uploading data and/or downloading data.
6. (previously presented) The method of claim 1, wherein a restricted bandwidth is allocated to one or more terminals for a prescribed time period.
7. (previously presented) The method of claim 1, wherein a restricted bandwidth is allocated to one or more terminals on the basis of a priority status allocated to the one or more terminals or a user account.
8. (previously presented) The method of claim 1, wherein the IP address of a user terminal is authenticated on the basis that the user terminal has previously been authenticated by the gateway using an encryption/decryption process.
9. (previously presented) The method of claim 1, further including the step of

monitoring all ports of access of said user terminal.

10.(previously presented) The method of claim 1, further including the step of enabling and/or disabling one or more ports of access of a user terminal.

11.(previously presented) The method of claim 1, further including the step of controlling access of a user terminal to the second communication network from a management terminal coupled to the first communication network.

12.(previously presented) The method of claim 1, further including the step of monitoring a period of time a user terminal has access to the second communication network.

13.(previously presented) The method of claim 1, further including the step of monitoring a quantity of data a user terminal uploads and/or downloads.

14.(previously presented) The method of claim 1, further including the step of monitoring a cost to a user of their user terminal having access to the second communication network.

15.(currently amended) A system for monitoring and controlling data transfer in communication networks, said system comprising:
one or more user terminals coupled to a first communication network;

a second communication network coupled to said first communication network via a gateway and a firewall;

wherein said firewall:

simultaneously monitors transfer of data between said one or more user terminals and said second communication network, ~~for~~ said user terminals having an authenticated IP address that has access to said second communication network, said authenticated IP address including authentication of a user; and

dynamically controls, in real time, bandwidth available to said one or more user terminals at least on the basis of the authenticated user.

16.(previously presented) The system of claim 15, wherein a single machine comprises both the gateway and the firewall.

17.(previously presented) The system of claim 15, wherein the firewall is in a different machine from the gateway.

18.(previously presented) The system of claim 15, wherein authentication of the IP address is carried out by the gateway.

19.(previously presented) The system of claim 18, wherein authentication employs an encryption/decryption process to authenticate a remote terminal.

20.(previously presented) The system of claim 15, wherein the firewall

simultaneously monitors all ports of access of one or more of said user terminals.

21.(previously presented) The system of claim 15, wherein a restricted bandwidth is allocated to a single user terminal.

22.(previously presented) The system of claim 15, wherein a restricted bandwidth is shared between a plurality of user terminals.

23.(previously presented) The system of claim 15, wherein a restricted bandwidth is allocated to a user account.

24.(previously presented) The system of claim 15, wherein bandwidth is restricted for uploading data and/or downloading data.

25.(previously presented) The system of claim 15, wherein said dynamic control of bandwidth available to said one or more user terminals occurs whilst maintaining communication of said one or more user terminals with said second communication network.

26.(currently amended) A gateway for monitoring and controlling data transfer in communication networks, said gateway comprising:

a firewall for permitting access to a second communication network for one or more user terminals coupled to a first communication network having an

authenticated IP address, said authenticated IP address including authentication of a user;

wherein said gateway monitors simultaneously at said firewall transfer of data between said one or more user terminals and said second communication network and dynamically controls, in real time, bandwidth available to said one or more user terminals at least on the basis of the authenticated user.

27.(previously presented) The gateway of claim 26, wherein the firewall simultaneously monitors all ports of access of one or more of said user terminals.

28.(previously presented) The gateway of claim 26, wherein the dynamic control of bandwidth available to said one or more user terminals occurs whilst maintaining communication of said one or more user terminals with said second communication network.

29. (previously presented) The gateway of claim 26, further comprising means for enabling and/or disabling one or more ports of access to each user terminal.